

2-in-1 Emergency Light



The *Energizer*® 2-in-1 Emergency Light is a versatile area light and directional light in one compact and highly reliable product. Designed for both outdoor and indoor use, its brightly colored finish and reflective panels ensure that it is easy to find in emergency situations. The area light mode provides broad, diffused light to illuminate larger spaces while maintaining an extremely long runtime and a red flashing light for signaling in emergency situations. The directional light mode provides a concentrated, direct light with a lengthy runtime and an excellent beam reach. The magnets around the lens allow handsfree use while signaling which is perfect for auto emergencies. Tough by design, the *Energizer*® 2-in-1 Light is durable and water resistant.

| Lumens | Runtime | Beam Distance | Drop | Water Ingress |
|---------------------------------------|-----------------------------|-----------------------------|----------------------------|------------------------------|
| <p>FL1 STANDARD 90 LUMENS</p> | <p>FL1 STANDARD 38h</p> | <p>FL1 STANDARD 65m</p> | <p>FL1 STANDARD 1m</p> | <p>FL1 STANDARD IPX4</p> |



| DESIGN BENEFITS |
|---|
| <ul style="list-style-type: none"> ✓ Combined area and spot modes in one product ✓ Durable construction ✓ High-visibility reflective panels ✓ Red flashing for signaling ✓ Magnets around the lens for handsfree use ✓ Floats |

| PERFORMANCE BENEFITS |
|--|
| <ul style="list-style-type: none"> ✓ LED technology ✓ Long runtime in spot mode ✓ Light floats in water |

| LIGHT AND POWER SOURCE |
|---|
| <ul style="list-style-type: none"> ✓ Features LED technology ✓ Operates on 2 AA batteries |

| BATTERY SPECIFICATIONS | |
|------------------------|------------------|
| Battery Type | ENR Max Alkaline |
| Battery Size | AA |
| Number of Cells | 2 |

| PRODUCT SPECIFICATIONS | |
|------------------------|---|
| Weight: | 86 Grams / 2.99 Ounces |
| Dimensions: | 170 mm x 58 mm x 58 mm 6.69" x 2.28" x 2.28" |

| BATTERY PERFORMANCE | | | |
|---------------------|-------------|-------------|-------------------|
| Modes | Lumens (lm) | Runtime (h) | Beam Distance (m) |
| Directional Spot-On | 90 | 38 | 65 |
| Area-On | 90 | 24 | N/A |

| ELECTRICAL CHARACTERISTICS | |
|----------------------------|----------------------------|
| Nominal Power Consumption: | 0.75 W |
| Batteries: | 2 AA Energizer E91 3.0V dc |
| LED Specifications: | LED 3.0V cc / 250 mA |

| DISCLAIMERS |
|---|
| <p>Tested according to ANSI/NEMA FL1 Standards. This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p> |

| Other Modes |
|-------------------------------|
| High, Area, Red Flash (1.5Hz) |

| CERTIFICATES AND COMPLIANCE | |
|-----------------------------|--|
| EMC, EN62471, FCC | |

Publish Date: 10-07-2020